

Product name : Heatless ink ST-350 Blue Ink  
SDS Number : 15A057

Date Prepared : Aug.04.2015  
Revision Date : Jan.28.2019

**1. PRODUCT AND COMPANY IDENTIFICATION**

Product Name : Heatless ink ST-350 Blue Ink  
Recommended use : Ink for ink jet printer  
  
Company : Sneed Coding Solutions  
22315 Gosling Rd,  
Spring, TX 77389  
  
Telephone number : 833-926-3464  
  
E-mail : support@sneedcoding.com

**2. HAZARDS IDENTIFICATION**

GHS Classification of the substance or mixture  
Flammable liquid : Category 2  
Serious eye damage/eye irritation : Category 1  
Specific target organ toxicity - Single exposure : Category 3 (Narcotic effect)

Label Elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : Highly flammable liquid and vapor.  
Causes serious eye damage.  
May cause drowsiness or dizziness.

Precautionary statements

Prevention : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.

Response : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.  
In case of fire: Use an appropriate extinguishing agent for extinction.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a POISON CENTER or doctor/physician if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.  
Immediately call a POISON CENTER or doctor/physician.

Storage : Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Store locked up.

Disposal : Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards : None known

Product name : Heatless ink ST-350 Blue Ink  
SDS Number : 15A057

Date Prepared : Aug.04.2015  
Revision Date : Jan.28.2019

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance or Mixture : Mixture

Ingredients

| Components | CAS No.      | Concentration (wt%) |
|------------|--------------|---------------------|
| Ethanol    | 64-17-5      | < 65                |
| 1-Propanol | 71-23-8      | < 25                |
| Dyestuff   | Confidential | < 10                |
| Acetone    | 67-64-1      | < 2.5               |
| 1-Butanol  | 71-36-3      | < 1.5               |

### 4. FIRST-AID MEASURES

Description of first aid measures

- Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Get medical advice/attention if you feel unwell.
- Skin contact : Wash thoroughly with soap and plenty of water while removing all contaminated clothes.  
If skin irritation or rash occurs: Get medical advice/attention.
- Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Remove contact lenses, if present and easy to remove. Continue to rinse for at least 15 minutes.  
Get medical attention immediately.
- Ingestion : Wash mouth with water and seek medical advice immediately.  
Do not induce vomiting.

Most important symptoms and effects, both acute and delayed  
: No further relevant information available.

Recommendations for immediate medical care and special treatment needed

Notes to physician : Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>), Dry chemical, Alcohol-resistant foam, Water spray.  
Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the substance or mixture

- : Carbon oxides, nitrogen oxides will form in fire.

Special protective equipment for firefighters

- : Wear suitable protective suit and self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Wear appropriate personal protective equipment as specified in section 8.  
Keep unnecessary peoples away. Isolate area. Ensure adequate ventilation.

Product name : Heatless ink ST-350 Blue Ink  
SDS Number : 15A057

Date Prepared : Aug.04.2015  
Revision Date : Jan.28.2019

Environmental precautions : Do not release into soil, sewers, river, or the public water courses.  
Methods and materials for containment and cleaning up :  
In the case of a cartridge: Not applicable.  
At the time of the leakage of contents: Absorb or cover with dry earth, sand or other non-combustible material and transfer to sealable containers. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. HANDLING AND STORAGE

Handling :  
Put on appropriate personal protective equipment (see Section 8).  
Prohibition of dropping and throwing.  
Avoid contact with skin, eyes and clothing.  
Do not breathe vapors. Use only in a well-ventilated area.  
Use a ventilation, local exhaust if vapor or aerosol will be generated.  
Keep away from fire, sparks and heated surfaces.  
Take precautionary measures against electrostatic discharges.  
Hygiene measures : When using do not eat or drink. Wash hands thoroughly after handling.  
Storage :  
Do not store ink in high or freezing temperature.  
Keep away from heat and direct sunlight.  
Do not store ink with acids, oxidizing agents or explosives.  
Keep containers tightly closed in a dry, cool and well-ventilated place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

| Components | CAS No. | OSHA PEL             | ACGIH TLV                     |
|------------|---------|----------------------|-------------------------------|
| Ethanol    | 64-17-5 | 1000 ppm, 1900 mg/m3 | STEL: 1000 ppm                |
| 1-Propanol | 71-23-8 | 200 ppm, 500 mg/m3   | TWA: 100 ppm                  |
| Acetone    | 67-64-1 | 1000 ppm, 2400 mg/m3 | TWA: 500 ppm<br>STEL: 750 ppm |
| 1-Butanol  | 71-36-3 | 100 ppm, 300 mg/m3   | TWA: 20 ppm                   |

Engineering controls :  
Engineering measures : Adequate ventilation should be provided so that exposure limits are not exceeded.  
Take precautionary measures against static discharge.  
Personal protective equipment :  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.  
Hand protection : Impermeable gloves.  
Eye protection : Safety glasses with side-shields. Goggles.  
Skin and body protection : Protective suit, Safety shoes.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Solvent type ink  
Color : Blue  
Odor : Alcohol odor  
pH : 6.5 - 8.5

Product name : Heatless ink ST-350 Blue Ink  
SDS Number : 15A057

Date Prepared : Aug.04.2015  
Revision Date : Jan.28.2019

Melting point : No data available  
Boiling point : 75 degree C  
Flash point : 12 degree C (Closed cup)  
Evaporation rate : No data available  
Flammability (solid, gas) : No data available  
Upper explosion limit : No data available  
Lower explosion limit : No data available  
Vapor pressure : No data available  
Vapor density : No data available  
Relative density : 0.84 (at 25 degree C)  
Water solubility : Insolubility  
Partition coefficient: n-octanol/water : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity : 2.3 - 2.8 mPa s (at 25 degrees C)

## 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions with proper storage and handling.  
Chemical stability : The product is stable under normal conditions.  
Possibility of hazardous reactions : No hazardous reactions with proper storage and handling.  
Conditions to avoid : High temperature, heat, sparks, flames and other sources of ignition. Oxidizing condition.  
Incompatible materials : No information available.  
Hazardous decomposition products : Carbon oxides, nitrogen oxides will form in fire.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity

|                                                             |   |                                    |               |                                 |
|-------------------------------------------------------------|---|------------------------------------|---------------|---------------------------------|
| Acute toxicity (oral)                                       | : | Ethanol                            | LD50 (rat)    | 7,060 mg/kg                     |
|                                                             |   | 1-Propanol                         | LD50 (rat)    | 3,830 mg/kg                     |
|                                                             |   | 1-Butanol                          | LD50 (rat)    | 1,227 mg/kg (calculation value) |
| Acute toxicity (dermal)                                     | : | Ethanol                            | LDLo (rabbit) | 20,000 mg/kg                    |
|                                                             |   | 1-Propanol                         | LD50 (rabbit) | >10,000 mg/kg                   |
| Acute toxicity (inhalation)                                 | : | Ethanol                            | LC50 (rat)    | 63,000 ppm/4h                   |
|                                                             |   | 1-Propanol                         | LC50 (rat)    | >9.8 mg/l/4h                    |
| Skin corrosion/irritation                                   | : | 1-Propanol                         | (rabbit)      | 72h; Slight                     |
|                                                             |   | 1-Butanol                          | (rabbit)      | 405 mg/24h; Moderate            |
| Serious eye damage/eye irritation                           | : | 1-Propanol                         | (rabbit)      | 72h; Severe                     |
|                                                             |   | 1-Butanol                          | (rabbit)      | 1.62 mg; Severe                 |
| Respiratory or skin sensitization                           | : | 1-Propanol                         | (guinea pig)  | Non-sensitizing                 |
| Germ cell mutagenicity                                      | : | No data available                  |               |                                 |
| Carcinogenicity                                             | : | NTP : Not listed.                  |               |                                 |
|                                                             |   | IARC : Ethanol: Group 1            |               |                                 |
|                                                             |   | EPA : 1-Butanol: D                 |               |                                 |
| Reproductive toxicity                                       | : | No data available                  |               |                                 |
| Specific target organ systemic toxicity - Single exposure   | : | May cause drowsiness or dizziness. |               |                                 |
| Specific target organ systemic toxicity - Repeated exposure | : | No data available                  |               |                                 |
| Aspiration hazard                                           | : | No data available                  |               |                                 |

Product name : Heatless ink ST-350 Blue Ink  
SDS Number : 15A057

Date Prepared : Aug.04.2015  
Revision Date : Jan.28.2019

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

|                  |   |            |                            |               |
|------------------|---|------------|----------------------------|---------------|
| Toxicity to fish | : | Ethanol    | LC50 (Pimephales promelas) | >100 mg/l/96h |
|                  | : | 1-Propanol | LC50 (Pimephales promelas) | >804 mg/l/96h |

Persistence and degradability : No data available  
Bioaccumulation : No data available  
Mobility in soil : No data available

## 13. DISPOSAL CONSIDERATIONS

Appropriate disposal methods : Dispose of waste material in accordance with local, state and federal pollution regulations.

Contaminated packaging : When disposing of an empty container, dispose after removing contents materials completely. Dispose of this material and its container according to your country law.

## 14. TRANSPORT INFORMATION

Class : Class 3  
UN number : 1210  
Packing group : II  
UN proper shipping name : Printing Ink

### Sea transport

#### IMDG-Code:

Class : Class 3  
UN number : 1210  
Packing group : II  
UN proper shipping name : Printing Ink  
Marine pollutant : No

### Air transport

#### ICAO-TI/IATA-DGR :

Class : Class 3  
UN number : 1210  
Packing group : II  
UN proper shipping name : Printing Ink

### Land transport

#### DOT :

Class : Class 3  
UN number : 1210  
Packing group : II  
UN proper shipping name : Printing Ink

## 15. REGULATORY INFORMATION

Follow all regulations in your country.

Product name : Heatless ink ST-350 Blue Ink  
SDS Number : 15A057

Date Prepared : Aug.04.2015  
Revision Date : Jan.28.2019

**Toxic Substances Control Act (TSCA)**

TSCA Status : All of the components of this product are listed on the TSCA Inventory.

**16. OTHER INFORMATION**

Literature Reference : SDS of raw material manufacturer  
NITE: Chemical Risk Information Platform  
3E: Ariel Research Tool

Revision date :

Further information

The information contained herein is based on the current knowledge. This Safety Data Sheet is intended to describe our products in correctness of safety requirements. It should not therefore be construed as guaranteeing specific properties. The data applies to only usual handling.